

6MB200

Professional Mid-bass Driver




KEY FEATURES

- 1.5" Voice coil
- 100 Watts continuous power handling
- 93 dB Sensitivity
- 125 - 4,500 Hz




GENERAL SPECIFICATIONS

Nominal Diameter	6" (152 mm)
Nominal impedance	8 ohms
Rated Power Handling	100 Watts
Program Power	200 Watts
Sensitivity 2.83V at 1m	93 dB
Recommended Hi Pass Crossover*	125 Hz*
<small>*For Full Power Handling</small>	<small>*12db Per Octave Crossover</small>
Frequency Response at -10dB	125 - 4,500 Hz
Voice Coil Diameter	1.5" (38 mm)
Voice Coil Wire	Cooper
Former Material	Kapton®
Frame Material	Stamped Steel



THIELE-SMALL PARAMETERS


Equivalent Volume	Vas	4.6 l
Excursion	Xmax	3.5 mm
Free Air Resonance	Fs	123.3 Hz
Mechanical Factor	Qms	24.36
Electrical Factor	Qes	1.32
Total Factor	Qts	1.25
Cone Area	Sd	154 cm ²
Mechanical Mass	Mms	11.97 g
Bl Factor	BL	7.15 Tm
Dc Resistance	Re	7.3 Ohms
Inductance	Le	0.72 mH at 1 kHz
Mechanical Mass Without Air	Mmd	10.89 g
Mechanical Compliance	Cms	0.139 mm/N



EXTRA INFO

Overall Diameter	6.53" (166 mm)
Front Mount Baffle Cutout	5.63" (143 mm)
Mounting Depth	2.6" (66 mm)
Overall Depth	2.91" (74 mm)
Net Weight	3.34 Lbs (1.51 kg)
Shipping Weight	3.62 Lbs (1.64 kg)
Carton Dimensions W x L x H	7.17" x 7.17" x 4.13" (182 x 182 x 105 mm)

Frequency Response Measured at 2.83V/1m



PRV AUDIO USA (USA and Export) PRV AUDIO BRAZIL (Brazilian Sales Only)
 FORT LAUDERDALE, FL SAO LEOPOLDO, RS
 support@prvaudio.com vendas@pvaudio.com.br
 www.prvaudio.com www.pvaudio.com.br