

MONOBLOCK AMPLIFIERS

The **RS Series** is designed for SPL competitors or those looking to bang harder on their daily systems.

These Class-D monoblock amps have an overbuilt power supply with true copper to provide optimum bass response.

1 CHANNEL

	RS500 BASS		RS900 BASS	
IMPEDANCE	1 Ohm	2 Ohm	1 Ohm	2 Ohm
RMS POWER @ 1Ω 14V	500W	---	900W	---
RMS POWER @ 2Ω 14V	350W	500W	550W	900W
RMS POWER @ 4Ω 14V	---	345W	---	540W
SUPPLY VOLTAGE	9-16 Volts		9-16 Volts	
FREQUENCY RESPONSE	5 - 200 Hz		5 - 200 Hz	
DIMENSIONS (WxDxH)	4.75" x 6.25" x 2.25"		6" x 6.25" x 2.25"	
WEIGHT	2 lbs		2.70 lbs	

1 CHANNEL

	RS3200 BASS		RS8200 BASS	
IMPEDANCE	1 Ohm	---	1 Ohm	---
RMS POWER @ 1Ω 14V	3200W	---	8200W	---
RMS POWER @ 2Ω 14V	2100W	---	4900W	---
RMS POWER @ 4Ω 14V	---	---	---	---
SUPPLY VOLTAGE	9-16 Volts		9-16 Volts	
FREQUENCY RESPONSE	5 - 200 Hz		5 - 250 Hz	
DIMENSIONS (WxDxH)	10.50" x 8.50" x 3.25"		17.50" x 8.50" x 3.25"	
WEIGHT	8.20 lbs		16 lbs	

FULLRANGE AMPLIFIERS

The **QS Series** amplifiers deliver powerful, clear mids and highs for stuntwalls, custom door panels, and large PRO Audio systems.

4 CHANNEL

	QS400.4		QS800.4		QS1200.4	
IMPEDANCE	2 Ohm		2 Ohm		2 Ohm	
RMS POWER @ 1Ω 14V	---		---		---	
RMS POWER @ 2Ω 14V	4x 100W		4x 220W		4x 310W	
RMS POWER @ 4Ω 14V	4x 70W		4x 140W		4x 160W	
BRIDGED POWER @ 4Ω 14V	2x 200W		2x 450W		2x 600W	
SUPPLY VOLTAGE	9-15 Volts		9-15 Volts		9-15 Volts	
FREQUENCY RESPONSE	20-25 kHz		20-25 kHz		20-24 kHz	
DIMENSIONS (WxDxH)	4"x5.40"x2"		8"x7.90"x2.65"		8.42"x7.90"x2.65"	
WEIGHT	1.18 lbs		3.80 lbs		4.50 lbs	

1 CHANNEL

	QS2000		QS3000		QS5000	
IMPEDANCE	1 Ohm	2 Ohm	1 Ohm	2 Ohm	1 Ohm	2 Ohm
RMS POWER @ 1Ω 14V	2000W	---	3000W	---	5000W	---
RMS POWER @ 2Ω 14V	1600W	1x 1800W	2100W	1x 1800W	3400W	1x 1800W
RMS POWER @ 4Ω 14V	---	1x 1100W	---	1x 1100W	---	1x 1100W
SUPPLY VOLTAGE	9-16 Volts		9-16 Volts		9-16 Volts	
FREQUENCY RESPONSE	20 - 20,000 Hz		20 - 20,000 Hz		20 - 15,000 Hz	
DIMENSIONS (WxDxH)	8.66" x 7.40" x 3"		8.66" x 7.30" x 3"		12" x 10.25" x 3"	
WEIGHT	4.80 lbs		5.10 lbs		9.50 lbs	

1 CHANNEL

	QS7000		QS9000		QS16000	
IMPEDANCE	1 Ohm	2 Ohm	1 Ohm	2 Ohm	1 Ohm	
RMS POWER @ 1Ω 14V	7000W	---	9000W	---	16,000W	
RMS POWER @ 2Ω 14V	4400W	7000W	6400W	9000W	10,000W	
RMS POWER @ 4Ω 14V	---	4500W	---	6200W	---	
SUPPLY VOLTAGE	9-16 Volts		9-16 Volts		9-16 Volts	
FREQUENCY RESPONSE	20 - 15,000 Hz		20 - 15,000 Hz		20 - 10,000 Hz	
DIMENSIONS (WxDxH)	17.25" x 10.25" x 3"		20" x 10.25" x 3"		24.25" x 10.25" x 3"	
WEIGHT	13.90 lbs		16.30 lbs		21 lbs	

COAXIAL SPEAKERS



MT6CX580CF-NDY-4

6.5" CARBON FIBER 2-WAY COAXIAL

500 Watts / 80 Watts
95 dB / 106 dB

MT8CX680CF-NDY-4

8" CARBON FIBER 2-WAY COAXIAL

600 Watts / 80 Watts
96 dB / 106 dB

BUILT TO PERFORM



MT6CX580-NDY-4

6.5" 2-WAY COAXIAL

500 Watts / 80 Watts
95 dB / 106 dB

MT8CX680-NDY-4

8" 2-WAY COAXIAL

600 Watts / 80 Watts
97 dB / 106 dB

SHALLOW SPEAKERS



MT6MR400CF-NDY-4 SLIM

6.5" NEODYMIUM MIDRANGE

400 Watts / 4 Ohm
97 dB

MT8MR400CF-NDY-4 SLIM

8" NEODYMIUM MIDRANGE

400 Watts / 4 Ohm
95 dB

CARBON FIBER SPEAKERS



6MR400CF-4

6.5" CARBON FIBER MIDRANGE

400 Watts / 4 Ohm
120 - 12,000 Hz

8MR450CF-4

8" CARBON FIBER MIDRANGE

450 Watts / 4 Ohm
95 - 10,000 HzGREAT FOR
OUTDOOR
APPLICATIONS

MOTORCYCLES / BOATS / OUTDOOR SYSTEMS / 4-WHEELERS / CAR AUDIO / UTV

SHALLOW TWEETER



TW400Ti-Nd-4 SLIM

1" NEODYMIUM SUPER TWEETER

120 Watts / 4 Ohm
105 dB

3" ROUNDED

1.22" MOUNTING DEPTH

CAR SPEAKERS



RS65-CX

6.5" 2-WAY COAXIAL

80 Watts RMS
45 - 20,000 Hz

RS65-PRO

6.5" FULL RANGE

100 Watts RMS
60 - 18,000 Hz

RS69-CX

6x9" 2-WAY COAXIAL

100 Watts RMS
40 - 20,000 Hz

RS69-CX

SUBWOOFERS



RS65-SUBD4

6.5" CAR SUBWOOFER

Xmax: 8.75 mm
300 Watts RMS
Dual 4 Ohm

RS8-SUBD4

8" CAR SUBWOOFER

Xmax: 14.5 mm
500 Watts RMS
Dual 4 Ohm

RS10-SUBD4

10" CAR SUBWOOFER

Xmax: 17.5 mm
1000 Watts RMS
Dual 4 Ohm

RS12-SUBD4

12" CAR SUBWOOFER

Xmax: 17.5 mm
1000 Watts RMS
Dual 4 Ohm

BASS AMPLIFIERS



RS1400 BASS

1 CH / MONOBLOCK AMP

1400 Watts RMS
1 Ohm

RS2200 BASS

1 CH / MONOBLOCK AMP

2200 Watts RMS
1 Ohm

100% COPPER OFC WIRES

ALL COLORS AVAILABLE IN 00, 0, 4 AND 8 GAUGE



- Made from pure oxygen-free non-recycled virgin copper.
- True size - meets the AWG (American Wire Gauge) industry standard requirements.
- Built to perform in extreme temperatures with minimum power loss.
- Soft-touch ultra-flexible PVC casing that allows positioning in tight spaces.

PREMIUM OFC SPEAKER WIRE

AVAILABLE IN
12, 14 AND 16 GAUGE

100ft Roll

SIMPLE INSTALLATION

Two conductor speaker wire - frosted black and tinted grey PVC jacket color coded by polarity for quick, easy and accurate installation

MINI AMPLIFIERS

The **MDX Series** amps deliver high-definition sound in a compact, reliable design, ideal for high-performance systems with limited space.

1 CHANNEL



MDX1800.1

MDX2500.1

	1 Ohm	2 Ohm	1 Ohm	2 Ohm
IMPEDANCE	1 Ohm	2 Ohm	1 Ohm	2 Ohm
RMS POWER @ 1Ω 14V	1x 1800W	---	1x 2600W	---
RMS POWER @ 2Ω 14V	1x 1100W	1x 1800W	1x 1850W	1x 2700W
RMS POWER @ 4Ω 14V	---	1x 1100W	---	1x 2000W
SUPPLY VOLTAGE	9-16 Volts		8-16 Volts	
FREQUENCY RESPONSE	10 - 25,000 Hz		10 - 25,000 Hz	
DIMENSIONS (WxDxH)	6.60" x 5.90" x 2.60"		8.50" x 5.90" x 2.60"	
WEIGHT	2.85 lbs		4.05 lbs	

2 CHANNELS



MDX1200.2

MDX2000.2

	1 Ohm	2 Ohm	1 Ohm	2 Ohm
IMPEDANCE	1 Ohm	2 Ohm	1 Ohm	2 Ohm
RMS POWER @ 1Ω 14V	2x 600W	---	2x 1000W	---
RMS POWER @ 2Ω 14V	2x 380W	2x 600W	2x 650W	2x 1000W
RMS POWER @ 4Ω 14V	---	2x 400W	---	2x 660W
BRIDGED RMS POWER @ 4Ω 14V	---	1x1200W	---	1x 2000W
BRIDGED RMS POWER @ 2Ω 14V	1x 1200W	---	1x 2000W	---
SUPPLY VOLTAGE	8-16 Volts		8-16 Volts	
FREQUENCY RESPONSE	10 - 20,000 Hz		10 - 22,000 Hz	
DIMENSIONS (WxDxH)	6.50" x 5.90" x 2.60"		8.50" x 5.90" x 2.60"	
WEIGHT	2.70 lbs		3.95 lbs	

4 CHANNELS



MDX1200.4

MDX2000.4

	1 Ohm	2 Ohm	1 Ohm	2 Ohm
IMPEDANCE	1 Ohm	2 Ohm	1 Ohm	2 Ohm
RMS POWER @ 1Ω 14V	4x 300W	---	4x 500W	---
RMS POWER @ 2Ω 14V	4x 200W	4x 300W	4x 320W	4x 500W
RMS POWER @ 4Ω 14V	---	4x 200W	---	4x 320W
BRIDGED RMS POWER @ 4Ω 14V	---	2x 600W	2x 1000W	2x 1000W
BRIDGED RMS POWER @ 2Ω 14V	2x 600W	---	---	---
SUPPLY VOLTAGE	8-16 Volts		8-16 Volts	
FREQUENCY RESPONSE	10 - 20,000 Hz		10 - 22,000 Hz	
DIMENSIONS (WxDxH)	6.75" x 5.90" x 2.60"		9.00" x 5.90" x 2.60"	
WEIGHT	2.75 lbs		3.85 lbs	

DIGITAL SIGNAL PROCESSOR



DSP 2.4X TEAM

- 2 INPUT CHANNELS
- 4 OUTPUT CHANNELS
- BUILT-IN REMOTE OUT (SEQUENCER)

DSP 2.8X TEAM

- 2 INPUT CHANNELS
- 8 OUTPUT CHANNELS
- BUILT-IN REMOTE OUT (SEQUENCER)

www.prvaudio.com

FOLLOW US ON SOCIAL MEDIA

FOR EXCLUSIVE GIVEAWAYS!



@prvaudio



@prvaudio



@prvaudiobrazil



@prvaudio

PRO AUDIO SPEAKERS

BRINGING BACK THE TRUE VALUE OF

PRO AUDIO SPEAKERS

6.5" PRO AUDIO MIDBASS

6MB400

400 Watts / 8 Ohm
94 dB

8" PRO AUDIO MIDRANGE

8MR400

400 Watts / 8 Ohm
96 dB

8" PRO AUDIO MIDBASS

8MB500

500 Watts / 4 & 8 Ohm
75 - 7,500 Hz

10" SHALLOW MIDRANGE

10MR650A-NDY

650 Watts / 8 Ohm
99 dB

NEODYMIUM MAGNET

BEST DOOR SPEAKER

EASY TO FIT / LIGHTWEIGHT

ALTO SERIES

BUILT TO PERFORM

HIGH POWER HANDLING

EXTENDED VOCAL RESPONSE

X SERIES

10" MIDRANGE

10MR1200X

1200 Watts / 8 Ohm
80 - 7,000 Hz

12" MIDRANGE

12MR1200X

1200 Watts / 8 Ohm
70 - 6,500 Hz

12" NEODYMIUM MIDRANGE

12MR2000X-NDY

2000 Watts / 8 Ohm
100 - 5,200 Hz

6.5" CAR SPEAKERS

HIGH PERFORMANCE **PROAudioOnWheels**

8" CAR SPEAKERS

6.5" BULLET SLIM MIDRANGE

6MR250B-4 SLIM

250 Watts / 4 Ohm
93.5 dB

6.5" BULLET MIDRANGE

6MR400-4 BULLET

400 Watts / 4 Ohm
95 dB

6.5" NEODYMIUM MIDRANGE

6MR400-NDY-4 BULLET

400 Watts / 4 Ohm
95.5 dB

BUILT TO PERFORM

6.5" MIDRANGE + SUPER TWEETERS

6BUNDLE BULLET

420 Watts / 120 Watts
95 dB / 104 dB

SOLD IN PAIRS SOLD IN PAIRS

1080 Watts

8" BULLET SLIM MIDRANGE

8MR400B-4 SLIM

400 Watts / 4 Ohm
93.5 dB

8" BULLET MIDRANGE

8MR500-4 BULLET

500 Watts / 4 Ohm
95 dB

8" NEODYMIUM MIDRANGE

8MR500-NDY-4 BULLET

500 Watts / 4 Ohm
97 dB

BUILT TO PERFORM

HORN DRIVERS

WG2000Py SLIM

2" MIDS & HIGHS DRIVER + HORN

150 Watts / 8 Ohm
1,000 - 17,000 Hz
Polyimide Diaphragm

WG175Py-Nd-4

1" MINI HORN DRIVER

150 Watts / 4 Ohm
1,600 - 20,000 Hz
Polyimide Diaphragm

WG2200Ph SLIM

2" MIDRANGE DRIVER + HORN

200 Watts / 8 Ohm
800 - 9,000 Hz
Phenolic Diaphragm

WG08-25

1" MINI WAVEGUIDE

1" Screw-on
1.72" Mounting Depth
3.31" x 3.31" x 1.95"

D250Ti-S

1" SCREW-ON TITANIUM DRIVER

100 Watts / 8 Ohm
1,800 - 20,000 Hz

WGP10-25 SLIM

1" SLIM WAVEGUIDE

1" Screw-on
1.75" Mounting Depth
4.15" x 4.15" x 2.07"

12" SPEAKERS

12" NEODYMIUM MIDBASS

12MB2000FT-NDY

2000 Watts / 8 Ohm
99.5 dB / 72 - 5,200 Hz

12" MIDBASS

12MB2000FT

2000 Watts / 8 Ohm
98 dB / 65 - 5,000 Hz

UNMATCHED VOCAL RESPONSE AT HIGH MIDBASS EXCURSION

SEALED BASKET SPEAKERS

6.5" SEALED BASKET MIDRANGE

6MR400SEAL PRO

400 Watts / 8 Ohm
96 dB

8" SEALED BASKET MIDRANGE

8MR500SEAL PRO

500 Watts / 8 Ohm
97 dB

CAR AUDIO COAXIAL SPEAKERS

6.5" 2-WAY COAXIAL

6CX380-4 SLIM

380 Watts / 4 Ohm
96 dB

8" 2-WAY COAXIAL

8CX380-4 SLIM

380 Watts / 4 Ohm
97 dB

6x9" 2-WAY COAXIAL

69CX380-4

380 Watts / 4 Ohm
97 dB

PORTABLE BT SPEAKERS

PS15 CLIP

BLUETOOTH SPEAKER

Pocket Size w/ clip
IPX7 Waterproof
15 Watts Speaker
20 Hours Playtime

PS36 MAGNET

BLUETOOTH SPEAKER

Magnetic w/ LED Bar
IPX6 Waterproof
2x 18 Watts Speaker
10 Hours Playtime

VINTAGE SPEAKER BOX

BLUETOOTH SPEAKER SYSTEM

Speaker Box
Microphone Input
2x 20 Watts Speaker
10 Hours Playtime

12" WOOFER

12" LOW FREQUENCY WOOFER

12W5000

5000 Watts
Available in 2 and 4 Ohm

DESIGNED TO WITHSTAND INTENSE SOUND PRESSURE